



5 Ton Outdoor Portable Heat Pump with Auxiliary Heat

PRODUCT FEATURES

REFRIGERATION

5 Ton Scroll Compressor
 Integrated Compressor Protection
 High Pressure and Low Pressure Cut-Outs

AUXILIARY HEAT - OPTION

Automatic change-over from Heat Pump to Aux. Heat
 7 KW Aux. Electrical Heat

ELECTRICAL

Power Connection Box with Terminal Block
 NOTE: Power cord to be field installed
 50 Amp Circuit Breaker for Unit Power Protection
 40 Amp Auxiliary Heat Breaker
 24V Thermostat with weatherproof enclosure

BLOWER/FILTERS

Multi-Speed ECM Evaporator Blower
 Static Capability Up to 0.7" ESP
 Totally Enclosed Condenser Fan Motor

CABINET

2" x 2" Steel Frame with Handle and Fork Pockets
 Wheel Pockets located in Frame for Stackable Storage (3 High Stack - Maximum)
 8-Inch Urethane Swivel Casters
 Two Swivel with Rotational Locking Pins, Two Swivel with Brakes

DUCT CONNECTIONS

Supply: 1 x 12" Dia. Duct Collar
 Return: 2 x 12" Dia. Duct Collar with integral Return Air Filter Frame
 Filter: (1) 14 x 25 x 1, Pleated

DRAIN

P-Trap with 3/4" Male Garden Hose Connector

TECHNICAL SPECIFICATIONS

Cooling Capacity:	60,300 BTUH
Aux. Heat Capacity:	7 KW
Voltage:	208-230V, 60Hz, 1PH
Amps:	40.1
Total Watts:	5020
Cooling Ambient:	Operating Range 25° to 115°
Cooling Capacity:	Total BTUH at 80°DB/67°WB Return air, 95°F Outdoor
EER:	11.9
Compressor:	Scroll
Compressor HP:	5
Compressor RLA:	26.4
Compressor LRA:	132
Evaporator CFM - High:	1600
Blower Type:	Centrifugal
Evaporator Motor:	3/4-HP
Condenser Fan:	Propeller
COND CFM:	1750
Condenser Motor:	1/4 HP
Condensate Removal:	Gravity Drain
Refrigerant Charge:	175 ozs. R-410A
Height:	52.5"
Width:	75.5" with handle
Depth:	42"
Net Weight:	710 lbs.

*Specifications subject to change without notice